

# Product Datasheet

## Eurorof SA Primer – Roller Applied

Sheet No: PDS-AP004  
Issued: 05/09/2024  
Pages: 1 of 1

### Description

Eurorof SA Primer is a Synthetic Rubber based primer, black in colour.

### Use

For preparation of new and existing substrates, to maximise the adhesion of the Alumasc range of Self Adhesive membranes. Metals must be grease and oil free. All substrates must be dust and debris free. Suitable for horizontal, sloping and vertical surfaces.

### Application

- Eurorof SA Primer is ready-for-use and must not be thinned or mixed with other products.
- The surfaces to be adhered must be dry and clean.
- The primer must only be applied in dry weather conditions at temperatures of at least 5°C, in a thin, even layer, with a brush or roller.
- Allow primer to dry. The primer is ready to bond when it feels dry to the touch and does not transfer to gloved finger tips. This time will vary dependant on temperature and climate conditions.
- It is important to directly position the surfaces correctly because any lateral adjustment is not possible after the first contact.
- Tools can be cleaned with ethyl acetate or white spirit.
- Do not use in conjunction with polystyrene foams.
- Primed areas must be covered within 12 hours or a further application of primer will be required.

### Product Data

Packaging	Drums: 25 Ltr
Storage	Store in a well-ventilated area, away from heat sources. Keep in airtight drums
Application	Manual Roller or Brush
Flash Point	-18°C
Shelf-life	12 months if stored at a cool temperature in an unopened drum.
Coverage	4 – 8 M <sup>2</sup> per Ltrs (100 - 200m <sup>2</sup> per drum)
Solids Content	32 – 36 %
Drying Time	30 Mins to 1 Hour (Depending on conditions)
Application Temp	5°C - 30°C

### Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from [www.alumascroofing.com](http://www.alumascroofing.com).

### Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: [technical@alumascroofing.com](mailto:technical@alumascroofing.com)

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.